



MATERIAL SAFETY DATA SHEET

Per 29 CFR 1910.1200

HEALTH	1	0-LEAST 1-SLIGHT
FLAMMABILITY	0	2-MODERATE 3-MILD
REACTIVITY	0	4-EXTREME

IDENTITY (As used on Label and List): **MOP STRIP 1217 EC**

SECTION I

EMERGENCY PHONE NUMBER:

Tel: (313) 933-4211

Fax: (313) 933-4454

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS:	OSHA	ACGH	OTHER	
<u>Case Number</u>	<u>Ingredients</u>		<u>%</u>	<u>TLV</u>
141-43-5	Ethanolamine		0 - 5	3 ppm
122-99-6	EG Phenyl Ether		5 - 20	
5324-84-5	Na Octanesulfonate		5 - 20	
5131-66-8	PG n-Butyl Ether		2 - 10	

SECTION III - PHYSICAL CHARACTERISTICS

BOILING POINT:	212F	SPECIFIC GRAVITY (H ₂ O=1):	0.987
VAPOR PRESSURE@20°C	N/A	VAPOR AIR DESITY (Air=1):	Less than Air
APPEARANDCE & ORDER:	Clear Solution, typical mild odor.	pH:	11 +/- 0.5
SOLUBILITY IN WATER:	Complete	MELTING POINT:	N/A
EVAPORATION RATE:	Slower than n-Butyl Acetate		

SECTION IV - FIRE & EXPLSION HAZARD DATA

FLASH POINT:	None
FLAMMABLE LIMITS:	LEL-N/A UEL-N/A
EXTINGIISHING MEDIA:	Foam or carbon dioxide or dry chemical
SPECIAL FIRE FIGHTING PROCEDURES:	Wear self-contained breathing apparatus with full face piece operated in pressure mode when fighting fires
UNUSUAL FIRE & EXPLOSION HAZARDS:	N/A

SECTION V - REACTIVITY DATA

STABILITY:	STABLE
CONDITIONS TO AVOID:	Avoid Freezing
INCOMPATIBLE MATERIALS:	None
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	N/A
HAZARDOUS POLYMERIZATION:	Will not occur.

